

BAU AD

Quartz sand primer for renders.



Description

BAU AD is a high-quality adhesion primer consisting of synthetic resin and quartz sand. Ideal for priming generally absorbent mineral surfaces before applying renders. It ensures a perfectly stable surface ready to be smoothed or levelled while at the same time enhancing the adhesion of the coating and regulating the water absorption of the substrate. Ideal substrate for all acrylic renders and cement mortars. Suitable for indoor and outdoor use. After application it creates a roughened alkaline resistant surface.

Coatings

- Acrylic plasters
- Cementitious coatings, renders
- Lime-based renders
- Gypsum-based coatings
- Water-colours
- Cementitious adhesives etc.

Substrates

- Concrete
- Bricks, brickwalls
- Lightweight concrete blocks
- Natural stones
- Ceramic tiles
- Wood
- Plasterboard
- Chipboard
- Cementitious coatings, renders
- Gypsum-based coatings etc.

Substrate preparation

Make sure that surfaces are level and sufficiently firm. Remove loose or detached fragments, dirt, oil, dust etc.

Instructions of use

The material is ready for use after thorough stirring of its whole mass. Apply with roller, brush or airless spraying machine.

Application is not recommended under extreme sunlight (temperature above 35°C) or rainfall and days when temperature is expected to drop below 5°C. After use remove material residues from tools using water while material is still fresh, or by other methods e.g. sanding or scraping when material has dried.

- **Application Temperature:** +5 up to +35 °C

Waiting Time: 15 up to 30min depending on the temperature and the porosity of the substrate



Technical features

Form:

emulsion

Color:

White, colored.

Consumption

≈ 0,1- 0,2 Kg/m² depending on the porosity of the substrate.

Packaging

Plastic pails of 10kg & 20 kg.

Storage

Preferably in shady and roofed locations, low in moisture. protected against ice, high temperature and exposure to sunlight for at least 12 months.

Volatile Organic Compounds (VOC)

According to Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory h, type WB is 30 g/lit for ready-to-use product. The ready -to-use product BAU AD contains a maximum of 30 g/lit VOC

TDS_BAU AD_12.2022



BAU AD

Quartz sand primer for renders.



Notes

Technical details, properties, recommendations and information on BAUSKIN products are supplied in good faith. They are based on the company's research and experience, provided that they are stored and applied under normal conditions. As the method of using materials as well as project and environment conditions are beyond the control of the company in each individual application setting, the product user is held solely responsible for the result of application. No responsibility under any legitimate relationship can be substantiated against the company, based on the information set out hereunder. Product users are advised to refer to the latest revision of the technical manuals available.

Exclusive distribution for Greece

BAUFOX Ltd

Email: info@baufox.com

www.baufox.com

Exclusive distribution for Cyprus

ALTO CEMENTOCHEMICA KA Ltd

Email: info@altocy.com

www.altocy.com

Frankfurt, Reg. No 312310 QM
Qualitätsmanagementsystem
Zertifiziert nach DIN EN ISO 9001



TDS_BAU AD_12.2022

