

BAU LOCK

Penetration primer for preparation of low absorption substrates.

Description

High quality acrylic water-based primer with very high penetration in porous or less porous surfaces. For increasing adhesion of cementitious adhesives, regulation of absorption and stabilization of the substrate. BAU LOCK is a primer that finds application in a large number of substrates and coating materials

Materials

- Cementitious adhesives
- Cementitious coatings
- Coatings of plaster
- Water soluble colors

Substrates

- Ceramic tiles
- Mosaics
- Metal
- Natural stones
- Asbestos cement slabs
- Timber surfaces
- Cementitious plaster and rendering
- Gypsum plaster and rendering
- Cellular concrete etc.

Substrate preparation

Ensure surfaces sufficiently stable. Remove loose, detached parts, dirt, oil and dust. Varnishes and paints must be removed completely.

Instructions of use

BAU LOCK can be diluted in water in a ratio of 1 part BAU LOCK with 3 parts of water when it is to be used as a stabilizer for surfaces. Use BAU LOCK diluted in water in a ratio of 1 part BAU LOCK with 1 part of water in cases of dense and poorly absorbent substrates in one coat. Apply BAU LOCK with brush, roller or spray.

Consumption

≈ 0,2 kg/m² depending on the absorbency of the substrate.



Technical features

Form:	liquid emulsion
Color	Light blue.
Density:	≈ 1,00 kg/lit
Ph value	9

Packaging

Plastic containers 20 kg.

Storage

In sheltered areas protected from frost, high temperature and direct sun exposure for at least 12 months from the date of production.

BAU LOCK

Penetration primer for preparation of low absorption substrates.

Notes

Technical details, properties, recommendations and information on BAUSKIN products are supplied in good faith. They are based on the company's research and experience, provided that they are stored and applied under normal conditions. As the method of using materials as well as project and environment conditions are beyond the control of the company in each individual application setting, the product used is held solely responsible for the result of application. No responsibility under any legitimate relationship can be substantiated against the company, based on the information set out hereunder. Product users are advised to refer to the latest revision of the technical manuals available.

Exclusive distribution for Greece:

BAUFOX Ltd
Email: info@baufox.com
www.baufox.com

Exclusive distribution for Cyprus:

ALTO CEMENTOCHEMICA K.A. Ltd
Email: info@altocy.com
www.altocy.com

Frankfurt, Reg. No 312310 QM
Qualitätsmanagementsystem
Zertifiziert nach DIN EN ISO 9001



TDS_BAU LOCK_12.2022